

# PERFORMANCE SPECIFICATIONS

Model	Heating Efficiency AFUE	Input Btuh Capacity [kW]	Output Btuh Capacity [kW]	Tons of add-on Cooling [kW]	Dimensions: HxWxD [inches]
<b>G61MP</b>					
G61MP-36B-045	94.10%	44,000 (12.9)	41,000 (12.0)	2.5-3 (8.8-10.5)	40 x 17-1/2 x 28-1/2
G61MP-36B-070	94.10%	66,000 (19.3)	62,000 (18.2)	2.5-3.5 (8.8-12.3)	40 x 17-1/2 x 28-1/2
G48MP-48C-090	94.10%	88,000 (25.8)	83,000 (24.3)	3-4 (10.5-14.0)	40 x 21 x 28-1/2
G61MP-48C-110	94.10%	110,000 (32.2)	104,000 (30.5)	3-4 (10.5-14.0)	40 x 21 x 28-1/2
G61MP-60C-090	94.10%	88,000 (25.8)	84,000 (24.6)	4-5 (14.0-17.5)	40 x 21 x 28-1/2
G61MP-60C-110	94.10%	110,000 (32.2)	104,000 (30.5)	4-5 (14.0-17.5)	40 x 21 x 28-1/2
G61MP-60D-135	94.10%	132,000 (38.7)	124,000 (36.3)	4-5 (14.0-17.5)	40 x 24-1/2 x 28-1/2
<b>G60DF/G60UH</b>					
G60DF-36A-070X	80.00%	66,000 (19.3)	54,000 (15.8)	2-3 (7.0-10.6)	40 x 14-1/2 x 28-1/2
G60DF-36B-090	80.00%	88,000 (25.8)	72,000 (21.1)	2-3 (7.0-10.6)	40 x 17-1/2 x 28-1/2
G60DF-48C-110	80.00%	110,000 (32.2)	90,000 (26.4)	2.5-4 (8.8-14.1)	40 x 21 x 28-1/2
G60UH-24A-070	80.00%	66,000 (19.3)	54,000 (15.8)	1.5-2 (5.3-7.0)	40 x 14-1/2 x 28-1/2
G60UH-36A-070X	80.00%	66,000 (19.3)	54,000 (15.8)	1.5-3 (5.3-10.6)	40 x 14-1/2 x 28-1/2
G60UH-36B-090	80.00%	88,000 (25.8)	72,000 (21.1)	2-3 (7.0-10.6)	40 x 17-1/2 x 28-1/2
G60UH-36C-110	80.00%	110,000 (32.2)	90,000 (26.4)	2-3 (7.0-10.6)	40 x 21 x 28-1/2
G60UH-48B-090X	80.00%	88,000 (25.8)	72,000 (21.1)	3-4 (10.6-14.1)	40 x 17-1/2 x 28-1/2
G60UH-60C-110X	80.00%	110,000 (32.2)	90,000 (26.4)	4-5 (14.0-17.6)	40 x 21 x 28-1/2
G60UH-60D-135	80.00%	132,000 (38.7)	108,000 (31.6)	4-5 (14.0-17.6)	40 x 24-1/2 x 28-1/2
<b>G51MP</b>					
G51MP-24B-045	92.10%	44,000 (12.9)	41,000 (12.0)	2-2.5 (7.0-8.8)	40 x 17-1/2 x 28-1/2
G51MP-36B-045	92.10%	44,000 (12.9)	41,000 (12.0)	2-3 (8.8-10.5)	40 x 17-1/2 x 28-1/2
G51MP-36B-070	92.10%	66,000 (19.3)	62,000 (18.2)	2-3 (8.8-10.5)	40 x 17-1/2 x 28-1/2
G51MP-36C-090	92.10%	88,000 (25.8)	82,000 (24.0)	2-3 (8.8-10.5)	40 x 21 x 28-1/2
G51MP-48C-090	92.10%	88,000 (25.8)	82,000 (24.0)	3-4 (10.5-14.0)	40 x 21 x 28-1/2
G51MP-48C-110	92.10%	110,000 (32.2)	103,000 (30.2)	3-4 (10.5-14.0)	40 x 21 x 28-1/2
G51MP-60C-090	92.10%	88,000 (25.8)	82,000 (24.0)	4-5 (14.0-17.5)	40 x 21 x 28-1/2
G51MP-60C-110	92.10%	110,000 (32.2)	103,000 (30.2)	4-5 (14.0-17.5)	40 x 21 x 28-1/2
G51MP-60D-135	92.10%	132,000 (38.7)	123,000 (36.0)	4-5 (14.0-17.5)	40 x 24-1/2 x 28-1/2
<b>G50DF</b>					
G50DF-24A-045X	80.00%	44,000 (12.9)	36,000 (10.5)	1.5-2 (5.3-7.0)	40 x 14-1/2 x 28-1/2
G50DF-36A-070X	80.00%	66,000 (19.3)	53,000 (15.5)	2-3 (7.0-10.6)	40 x 14-1/2 x 28-1/2
G50DF-36B-090	80.00%	88,000 (25.8)	71,000 (20.8)	2-3 (7.0-10.6)	40 x 17-1/2 x 28-1/2
G50DF-48C-090X	80.00%	88,000 (25.8)	71,000 (20.8)	3-4 (10.6-14.1)	40 x 21 x 28-1/2
G50DF-48C-110	80.00%	110,000 (32.2)	89,000 (26.1)	2-4 (7.0-14.1)	40 x 21 x 28-1/2
G50DF-60C-110	80.00%	110,000 (32.2)	90,000 (26.4)	4-5 (14.1-17.6)	40 x 21 x 28-1/2
G50DF-60D-135	80.00%	132,000 (38.7)	107,000 (31.3)	4-5 (14.1-17.6)	40 x 24-1/2 x 28-1/2

Note: Due to Lennox' ongoing commitment to quality, all specifications, ratings and dimensions are subject to change.

# PERFORMANCE SPECIFICATIONS

Model	Heating Efficiency AFUE	Input Btuh Capacity [kW]	Output Btuh Capacity [kW]	Tons of add-on Cooling [kW]	Dimensions: HxWxD [inches]
<b>G50UH</b>					
G50UH-24A-045X	80.00%	44,000 (12.9)	35,000 (10.2)	1.5-2 (5.3-7.0)	40 x 14-1/2 x 28-1/2
G50UH-24A-070	80.00%	66,000 (19.3)	54,000 (15.8)	1.5-2.5 (5.3-8.8)	40 x 14-1/2 x 28-1/2
G50UH-36A-070X	80.00%	66,000 (19.3)	53,000 (15.5)	2-3 (7.0-10.6)	40 x 14-1/2 x 28-1/2
G50UH-36B-090	80.00%	88,000 (25.8)	71,000 (20.8)	2-3 (7.0-10.6)	40 x 17-1/2 x 28-1/2
G50UH-36C-110	80.00%	110,000 (32.2)	88,000 (25.8)	2-3 (7.0-10.6)	40 x 21 x 28-1/2
G50UH-48B-090X	80.00%	88,000 (25.8)	71,000 (20.8)	3-4 (10.6-14.1)	40 x 17-1/2 x 28-1/2
G50UH-48C-110	80.00%	110,000 (32.2)	87,000 (25.5)	3-4 (10.6-14.1)	40 x 21 x 28-1/2
G50UH-48C-135	80.00%	132,000 (38.7)	106,000 (31.0)	2-4 (7.0-14.1)	40 x 21 x 28-1/2
G50UH-60C-110	80.00%	110,000 (32.2)	88,000 (25.8)	4-5 (14.0-17.6)	40 x 21 x 28-1/2
G50UH-60D-135	80.00%	132,000 (38.7)	107,000 (31.3)	4-5 (14.0-17.6)	40 x 24-1/2 x 28-1/2
G50UH-60D-155	80.00%	154,000 (45.1)	122,000 (35.7)	4-5 (14.0-17.6)	40 x 24-1/2 x 28-1/2
<b>G43UF</b>					
G43UF-24B-045	92.10%	44,000 (12.9)	40,300 (11.8)	1.5-2 (5.3-7.0)	40 x 17-1/2 x 28-1/2
G43UF-24B-070	90.00%	66,000 (19.3)	61,000 (17.9)	1.5-2 (5.3-7.0)	40 x 17-1/2 x 28-1/2
G43UF-36B-070	92.10%	66,000 (19.3)	62,000 (18.2)	2-3 (8.8-10.5)	40 x 17-1/2 x 28-1/2
G43UF-36C-090	92.10%	88,000 (25.8)	82,000 (24.0)	2-3 (7.0-10.5)	40 x 21 x 28-1/2
G43UF-36C-090H	90.00%	88,000 (25.8)	81,000 (23.7)	2-3 (7.0-10.5)	40 x 21 x 28-1/2
G43UF-48C-090	92.10%	88,000 (25.8)	82,000 (24.0)	3-4 (10.5-14.0)	40 x 21 x 28-1/2
G43UF-48C-110	92.10%	110,000 (32.2)	103,000 (30.2)	3-4 (10.5-14.0)	40 x 21 x 28-1/2
G43UF-48C-110H	90.00%	110,000 (32.2)	101,000 (29.6)	3-4 (10.5-14.0)	40 x 21 x 28-1/2
G43UF-60C-110	92.10%	110,000 (32.2)	103,000 (30.2)	4-5 (14.0-17.5)	40 x 21 x 28-1/2
G43UF-60D-135	92.10%	132,000 (38.7)	123,000 (36.0)	4-5 (14.0-17.5)	40 x 24-1/2 x 28-1/2
<b>G40DF/G40UH</b>					
G40DF-24A-045X	80.00%	44,000 (12.9)	36,000 (10.5)	1.5-2 (5.3-7.0)	40 x 14-1/2 x 28-1/2
G40DF-36A-045	80.00%	44,000 (12.9)	35,000 (10.3)	2-3 (7.0-10.6)	40 x 14 1/2 x 28 1/2
G40DF-36A-070X	80.00%	66,000 (19.3)	53,000 (15.5)	2-3 (7.0-10.6)	40 x 14-1/2 x 28-1/2
G40DF-36B-090	80.00%	88,000 (25.8)	71,000 (15.5)	2-3 (7.0-10.6)	40 x 17-1/2 x 28-1/2
G40DF-48B-070	80.00%	66,000 (19.3)	53,000 (15.5)	3-4 (10.6-14.1)	40 x 17 1/2 x 28 1/2
G40DF-48C-090X	80.00%	88,000 (25.8)	71,000 (15.5)	3-4 (10.6-14.1)	40 x 21 x 28-1/2
G40DF-48C-110X	80.00%	110,000 (32.2)	89,000 (26.1)	2.5-4 (8.8-14.1)	40 x 21 x 28-1/2
G40DF-60C-110X	80.00%	110,000 (32.2)	90,000 (26.4)	4-5 (14.1-17.6)	40 x 21 x 28-1/2
G40DF-60D-135	80.00%	132,000 (38.7)	107,000 (31.3)	4-5 (14.1-17.6)	40 x 24-1/2 x 28-1/2
G40UH-24A-045X	80.00%	44,000 (12.9)	36,000 (10.5)	1.5-2 (5.8-7.0)	40 x 14-1/2 x 28-1/2
G40UH-24A-070	80.00%	66,000 (19.3)	54,100 (15.6)	1.5-2 (5.8-7.0)	40 x 14-1/2 x 28-1/2
G40UH-36A-045	80.00%	44,000 (12.9)	35,900 (10.5)	2-3 (7.0-10.6)	40 x 14 1/2 x 28 1/2
G40UH-36A-070X	80.00%	66,000 (19.3)	54,100 (15.6)	2-3 (7.0-10.6)	40 x 14-1/2 x 28-1/2
G40UH-36B-090	80.00%	88,000 (25.8)	72,100 (21.1)	2-3 (7.0-10.6)	40 x 17-1/2 x 28-1/2
G40UH-36C-110	80.00%	110,000 (32.2)	90,200 (26.4)	2-3 (7.0-10.6)	40 x 21 x 28-1/2
G40UH-48B-070	80.00%	66,000 (19.3)	54,100 (15.6)	2-4 (7.0-14.1)	40 x 17 1/2 x 28 1/2
G40UH-48B-090X	80.00%	88,000 (25.8)	72,100 (21.1)	3-4 (10.6-14.1)	40 x 17-1/2 x 28-1/2
G40UH-48C-110	80.00%	110,000 (32.2)	88,500 (25.9)	3-4 (10.6-14.1)	40 x 21 x 28-1/2
G40UH-48C-135	80.00%	132,000 (38.7)	106,900 (31.3)	2.5-4 (8.8-14.1)	40 x 21 x 28-1/2
G40UH-60C-110X	80.00%	110,000 (32.2)	89,400 (26.2)	4-5 (14.1-17.6)	40 x 21 x 28-1/2
G40UH-60D-135	80.00%	132,000 (38.7)	106,900 (31.3)	4-5 (14.1-17.6)	40 x 24-1/2 x 28-1/2
G40UH-60D-155	80.00%	154,000 (45.1)	124,700 (36.5)	4-5 (14.1-17.6)	40 x 24-1/2 x 28-1/2

Note: Due to Lennox' ongoing commitment to quality, all specifications, ratings and dimensions are subject to change. Low-NOx units (labeled "X" in the model number) meet California Nitrogen Oxides standards.