

T-CLASS™ R-22 AC/HP PERFORMANCE SPECIFICATIONS

			COOLING DATA ^{2, 3}			HEATING DATA ⁴			PHYSICAL DATA		
	Nominal Tonnage		Sound Rating dB ¹	ARI Rated Cap. [Btuh]	Efficiency [SEER]	Efficiency [EER]	Efficiency [HSPF]	Capacity [Btuh]	COP	Dimensions H x W x L [inches]	Ship. Wt. [lbs.]
	Model										
AIR CONDITIONERS	3	TSA036S2	76	34,800	13.00	11.00	—	—	—	33.25 x 24.25 x 24.25	141
	3.5	TSA042S2	79	41,500	13.00	11.00	—	—	—	29.25 x 28.25 x 28.25	171
	4	TSA048S2	79	45,500	13.00	11.00	—	—	—	37.25 x 28.25 x 28.25	191
	5	TSA060S2	79	58,000	13.00	11.00	—	—	—	33.25 x 28.25 x 28.25	216
HEAT PUMPS	3	TPA036S2	76	35,200	13.00	11.00	7.7	33,800	3.58	33.25 x 24.25 x 24.25	178
	4	TPA048S2	80	50,500	13.00	11.00	7.7	47,500	3.42	37 x 28.25 x 28.25	248
	5	TPA060S2	80	57,000	13.00	11.00	7.7	55,000	3.30	43.25 x 32.25 x 32.25	298

T-CLASS R-410A AC/HP PERFORMANCE SPECIFICATIONS

			COOLING DATA ^{2, 3}			HEATING DATA ⁴			PHYSICAL DATA		
	Nominal Tonnage		Sound Rating dB ¹	ARI Rated Cap. [Btuh]	Efficiency [SEER] ⁵	Efficiency [EER]	Efficiency [HSPF] ⁶	Capacity [Btuh]	COP	Dimensions H x W x L [inches]	Ship. Wt. [lbs.]
	Model										
AIR CONDITIONERS	3	TSA036S4	76	33,800	13.00	10.90	—	—	—	29.25 x 24.25 x 24.25	135
	3.5	TSA042S4	79	40,500	13.00	10.90	—	—	—	29.25 x 28.25 x 28.25	178
	4	TSA048S4	79	47,000	13.00	11.00	—	—	—	37.25 x 28.25 x 28.25	194
	5	TSA060S4	79	59,000	13.00	11.00	—	—	—	33.25 x 28.25 x 28.25	218
HEAT PUMPS	3	TPA036S4	76	34,200	13.00	10.85	8.0	34,200	3.60	33.25 x 24.25 x 24.25	180
	3.5	TPA042S4	80	41,500	13.50	11.00	8.0	41,500	3.48	33.25 x 28.25 x 28.25	220
	4	TPA048S4	80	48,000	13.00	11.00	7.7	45,500	3.36	37.25 x 28.25 x 28.25	250
	5	TPA060S4	80	58,500	13.00	10.90	7.7	56,500	3.34	43.25 x 32.25 x 32.25	255

T-CLASS R-410A HIGH-EFFICIENCY AC/HP PERFORMANCE SPECIFICATIONS

			COOLING DATA ^{2, 3}			HEATING DATA ⁴			PHYSICAL DATA		
	Nominal Tonnage		Sound Rating dB ¹	ARI Rated Cap. [Btuh]	Efficiency [SEER] ⁷	Efficiency [EER]	Efficiency [HSPF] ⁸	Capacity [Btuh]	COP	Dimensions H x W x L [inches]	Ship. Wt. [lbs.]
	Model										
AIR CONDITIONERS	3	TSA036H4	76	34,000	14.00	12.00	—	—	—	37.25 x 28.25 x 28.25	164
	3.5	TSA042H4	78	41,500	14.00	12.00	—	—	—	29.25 x 28.25 x 28.25	198
	4	TSA048H4	78	49,000	14.00	12.00	—	—	—	37.25 x 28.25 x 28.25	221
	5	TSA060H4	80	58,000	14.00	12.00	—	—	—	33.25 x 32.25 x 32.25	238
HEAT PUMPS	3	TPA036H4	79	34,600	14.00	12.00	8.2	35,200	3.64	29.25 x 32.25 x 32.25	212
	3.5	TPA042H4	79	42,500	14.00	12.00	8.2	45,500	3.66	37 x 32.25 x 32.25	257
	4	TPA048H4	80	49,000	14.00	12.00	8.2	47,000	3.6	37 x 32.25 x 32.25	262
	5	TPA060H4	80	58,500	14.00	12.00	8.2	55,000	3.5	43.25 x 32.25 x 32.25	307

¹Sound rating number in accordance with test conditions included in ARI Standard 270.

²5-ton-and-under equipment certified in accordance with ULE certification program, which is based on ARI Standard 210/240.

³Cooling ratings, 95°F (35°C) outdoor air temperature and 80°F (27°C) db/67°F (19°C) wb entering indoor coil air.

⁴High-temperature heating ratings, 47°F (8°C) db/43°F (6°C) wb outdoor air temperature and 70°F (21°C) entering indoor coil air.

⁵Up to 14.00 SEER when the T-Class TSA060S4 split system is matched with the CBX26UH-060 air handler.

⁶Up to 8.2 HSPF when the T-Class TPA036S4 split system is matched with the CR33-50/60C-F 4 coil and G61MPV-36C-090 furnace.

⁷Up to 15.20 SEER when the T-Class TSA036H4 split system is matched with the CX34-49C and G71MPP-36C-090 furnace.

⁸Up to 9.00 HSPF when the T-Class TPA042H4 split system is matched with the CX34-62D and G60UHV-60D-135 furnace.

Note: Due to Lennox' ongoing commitment to quality, all specifications, ratings and dimensions are subject to change.